

ATTESTATION OF CONFORMITY

No. 25AE121374E002

The submitted sample of below equipment has been tested in according to Electromagnetic Compatibility Directive 2014/30/EU with the following standards. The test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the principal protection requirement of the EC Council Directive of 2014/30/EU.

Report No. : E04A25121374E00201
Applicant : VTAC EUROPE LTD
Address : Bulgaria, Plovdiv 4000, Bul.L.Karavelow 9B
Manufacturer : VTAC EUROPE LTD
Address : Bulgaria, Plovdiv 4000, Bul.L.Karavelow 9B
Description of Product : Portable Power Station
Model No. : VT-300011, VT-25001
Trade Mark : 
Rating : See the Attachment for details
Test Standards : EN 55032:2015/A1:2020
EN 55035:2017/A11:2020
EN IEC 61000-3-2:2019/A2:2024
EN 61000-3-3:2013/A2:2021

After preparation of the necessary technical documentation as well as the EU declaration of conformity, the CE marking can be affixed on the product if all relevant effective EU-directives or regulations related to CE marking have been complied with. The EU declaration of conformity is issued under the sole responsibility of the applicant or manufacturer.



Test Laboratory

Shawn Wen

Laboratory Manager

Date of Issue: January 08, 2026

This attestation of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the production of the products.

Guangdong Global Testing Technology Co., Ltd.

Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake
Park, Dongguan city, Guangdong, People's Republic of China, 523808

Web: www.gtgroup.com E-mail: info@gtgroup.com Tel.: 86-4007558988

No. 25AE121374E002

Attachment:

Model	Ratings	Difference	Extended battery pack ratings
VT-300011	Battery: 2560Wh, 51.2V --- Power Input/Output: 40-58.8V --- 50A charge, 70A discharge[max.] Discharge temperature range: -20-45°C Charge temperature range: 0-45°C AC Input: 220-240V~, 50/60Hz, 10A max., 2300W max. Solar/Car input x2: 13-45V --- 12A max., 800W max. AC socket x3: 220-240V~, 50/60Hz, 16A max., 3000W max. AC socket [Bypass Mode]: 220-240V~, 50/60Hz, 10A max., 2300W max. Cigarette lighter output/DC 5521 total: max. 126W Cigarette lighter output: 12.6V --- 10A max., 126W max. DC 5521 output x2: 12.6V3A, 40.8W max. Anderson terminal output: 12.6V --- 30A max., 378W max. USB-A1/A2 output: 5V --- 3A, 9V --- 2A, 12V --- 1.5A, 18W max. USB-C1/C2 output: 5/9/12/15V --- 3A, 20V --- 5A, 100W max. USB-A3/A4 output: 5V --- 2.4A, 12W max.	With Battery pack expansion port (Extended battery pack model: VT-25001)	Energy capacity: 2560Wh Nominal capacity: 50Ah Nominal voltage: 51.2Vd.c. Power port-input/output: 40-58.8Vd.c., 50A charge, 70A discharge (max.) Discharge temperature range: -20-45°C Charge temperature range: 0-45°C IFpP/41/150/102/[16 S]E/-20+50/90