

ATTESTATION OF CONFORMITY



Attestation No. 23AE040132W002

The submitted sample of below equipment has been tested in according to Radio Equipment Directive 2014/53/EU with the following standards. The test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the principal protection requirement of the EC Council Directive of 2014/53/EU.

Report No. : E01A23040132E00101, E01A23040132R00101, E01A23040132R00102, E01A23040132H00101, SZES230200050301

Applicant : CE LINK LIMITED

Address : ROOM 2204 22/F TUNG CHIU COMMERCIAL CENTER 193 LOCKHART ROAD WANCHAI HONG KONG SAR CHINA

Manufacturer : Dongguan Hinen New Energy Technology Co., Ltd

Address : No.24 Dongkang Road, Dalingshan Town, Dongguan City, Guangdong Province, China

Description of Product : Portable Power Station

Trade Mark : **CE-LINK®**, hinen

Model No. : SR03KWL-SG1-EU, PS3000 Max-GE, SR03KWL-SG1-FR, PS3000 Max-FR, XP2-3000, SFA30EU, HJ6003, Li3.0EU, P3000EU, PLZ-I0007-DE, PLZ-I0007B-DE, PLZ-I1007-DE, PLZ-I1007B-DE, PLZ-I0007-EU, PLZ-I0007B-EU, PLZ-I1007-EU, PLZ-I1007B-EU, PL-I0007-DE, PL-I0007B-DE, PL-I1007-DE, PL-I1007B-DE, PL-I0007-EU, PL-I0007B-EU, PL-I1007-EU, PL-I1007B-EU, SFA30FR, PLZ-I0007-FR, PLZ-I0007B-FR, PLZ-I1007-FR, PLZ-I1007B-FR, PL-I0007-FR, PL-I0007B-FR, PL-I1007-FR, PL-I1007B-FR, SFA30ZA, HJ6003, UPS3000, PLZ-I0007-ZA, PLZ-I0007B-ZA, PLZ-I1007-ZA, PLZ-I1007B-ZA, PL-I0007-ZA, PL-I0007B-ZA, PL-I1007-ZA, PL-I1007B-ZA, SR03KWL-SG1-ZA, PS3000 Max-ZA, SR03KWL-SG2-EU, PS3000-GE, SR03KWL-SG2-FR, PS3000-FR, SFB30EU, SFB30FR, KD30KWZA, SFB30ZA, UPS3000-ZA, SR03KWL-SG2-ZA, PS3000-ZA

Input Rating : See the Attachment for details

Test Standards : EN 55032:2015+A11:2020+A1:2020, EN 55035: 2017+A11:2020
EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021
ETSI EN 301 489-1 V2.2.3 (2019-11), ETSI EN 301 489-17 V3.2.4 (2020-09)
ETSI EN 300 328 V2.2.2: 2019, EN 62479: 2010, EN 50663: 2017
EN IEC 62368-1: 2020+ A11: 2020

After preparation of the necessary technical documentation as well as the EU declaration of conformity, the CE marking as below can be affixed on the product if all relevant effective EU-directives or regulations related to CE marking have been complied with. The EU declaration of conformity is issued under the sole responsibility of the applicant or manufacturer.



This attestation of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the production of the products.

Dongguan Anci Electronic Technology Co., Ltd.

Add.: 1-2 Floor, Building A, No.11, Headquarters 2 Road, Songshan Lake

Hi-tech Industrial Development Zone, Dongguan City, Guangdong Pr., China.

Web: www.gtgggroup.com E-mail: info@gtgggroup.com Tel:86-4007558988

Attestation No. 23AE040132W002

Attachment:

Model	Ratings	Difference	Extended battery pack ratings
SR03KWL-SG1-EU, PS3000 Max-GE, SR03KWL-SG1-FR, PS3000 Max-FR,XP2-3000, SFA30EU, HJ6003, Li3.0EU, P3000EU, PLZ-I0007-DE, PLZ-I0007B-DE, PLZ-I1007-DE, PLZ-I1007B-DE, PLZ-I0007-EU, PLZ-I0007B-EU, PLZ-I1007-EU, PLZ-I1007B-EU, PL-I0007-DE, PL-I0007B-DE, PL-I1007-DE, PL-I1007B-DE, PL-I0007-EU, PL-I0007B-EU, PL-I1007-EU, PL-I1007B-EU, SFA30FR, PLZ-I0007-FR, PLZ-I0007B-FR, PLZ-I1007-FR, PLZ-I1007B-FR, PL-I0007-FR, PL-I0007B-FR, PL-I1007-FR, PL-I1007B-FR, SFA30ZA, HJ6003, UPS3000, PLZ-I0007-ZA, PLZ-I0007B-ZA, PLZ-I1007-ZA, PLZ-I1007B-ZA, PL-I0007-ZA, PL-I0007B-ZA, PL-I1007-ZA, PL-I1007B-ZA, SR03KWL-SG1-ZA, PS3000 Max-ZA	Battery: 2560Wh, 51.2V --- Power Input/Output:40-58.8V --- 50A charge, 70A discharge[max.] Discharge temperature range:-20-45℃ Charge temperature range:0-45℃ AC Input: 220-240V~,50/60Hz,10A max., 2300W max. Solar/Car input x2:13-45V --- 12A max.,800W max. AC socket x3: 220-240V~,50/60Hz,16A max.,3000W max. AC socket [Bypass Mode]: 220-240V~, 50/60Hz, 10A max., 2300W max. Cigarette lighter output/DC 5521 total: max.126W Cigarette lighter output: 12.6V --- 10A max.,126W max. DC 5521 output x2:12.6V3A, 40.8W max. Anderson terminal output: 12.6V --- 30A max. , 378W max. USB-A1/A2 output: 5V --- 3A, 9V --- 2A, 12V --- 1.5A, 18W max. USB-C1/C2 output: 5/9/12/15V --- 3A, 20V --- 5A, 100W max. USB-A3/A4 output: 5V --- 2.4A, 12W max.	With Battery pack expansion port (Extended battery pack model: SA2KW5L-BG1-UV, PS2500B, 2500 Pack, EL8840, HJ6004, PL-I0005, PL-I0005B,PL-I100 5,PL-I1005B,PL-Z-I1005,PLZ-I1005 B,PPT2500B,PX25 00,SFD25EU,SFD2 5US,TTXB2500, XP2-EP2560)	Energy capacity: 2560Wh Nominal capacity: 50Ah Nominal voltage: 51.2Vd.c. Power port-input/output: 40-58.8Vd.c., 50A charge, 70A discharge (max.) Discharge temperature range:-20-45℃ Charge temperature range: 0-45℃ IFpP/41/150/102/[16S]E/-20+5 0/90
SR03KWL-SG2-EU, PS3000-GE, SR03KWL-SG2-FR, PS3000-FR, SFB30EU, SFB30FR, KD30KWZA, SFB30ZA, UPS3000-ZA, SR03KWL-SG2-ZA, PS3000-ZA	Battery: 2560Wh, 51.2V --- Discharge temperature range:-20-45℃ Charge temperature range:0-45℃ AC Input: 220-240V~,50/60Hz,10A max., 2300W max. Solar/Car input x2:13-45V --- 12A max.,800W max. AC socket x3: 220-240V~,50/60Hz,16A max.,3000W max. AC socket [Bypass Mode]: 220-240V~, 50/60Hz, 10A max., 2300W max. Cigarette lighter output/DC 5521 total: max.126W Cigarette lighter output: 12.6V --- 10A max.,126W max. DC 5521 output x2:12.6V3A, 40.8W max. Anderson terminal output: 12.6V --- 30A max. , 378W max. USB-A1/A2 output: 5V --- 3A, 9V --- 2A, 12V --- 1.5A, 18W max. USB-C1/C2 output: 5/9/12/15V --- 3A, 20V --- 5A, 100W max. USB-A3/A4 output: 5V --- 2.4A, 12W max.	Without Battery pack expansion port	N/A